

5th Floor,
Yutian Building,
No. 18 Yangtian Road,
Xin'an Street, Baoan District,
Shenzhen, Guangdong.

SHENZHEN ISD TECHNOLOGY CO.,LTD
深圳艾斯特创新科技有限公司



WWW.ISDT.CO

ISDT
Powerful Charging Made Easy

FD200

SMART
DISCHARGER



Max discharge power: 200W
Discharge current: 5/10/15/20/25A (APP adjustable 0.5-5A current)
Support cells: 2-8S
Bluetooth support: BLE4.0 above

Size: 140x60x100mm

SP3060

SMART
POWER



Rated output current: 60A
Output power: 1800W @150V-240VAC
720W @100V-150VAC

Size: 115x110x257mm

BG-8S

SMART
BATTERY CHECKER



Working voltage: 5.0V-36V
Input voltage 1s: 0.8V-15V
Input voltage 2-8S: 0.8V-4.8V
Support USB charging: QC 2.0 / 3.0, BC1.2,
Maximum output 12V/2A
Supported Batt. Type: Li-Iv (1-8S) / LiPo (1-8S) / LiFe(1-8S)
Lilon (1-8S) / NiMH/Cd(1-10S)

Size: 80 X 55 X 19 mm

CM1620

CHARGING
MODULE



Charging power: 1000W
Charging current: 20A
Balance current: 2-16S

Size: 105x165x41 mm

Industry



B80

SMART
POWER

Output power: 3000W @ 220V / 1250W @ 110V
Output voltage: 20V - 80V DC
Input: 100V-240V AC
Balance current: 6-22S

Size: 356x136x164 mm

X16

SMART
POWER



Max. charging power: 1100Wx2 @220VAC
800Wx2 @110VAC
Charging current: 20Ax2
Balance current: 2-16S

Size: 276x246x82 mm

INNOVATIVE

SMART DEVICE

ISDT
Powerful Charging Made Easy

608AC

AC/DC
SMART
CHARGER



Charging Power: AC 50W
DC 200W
Charging Current: 8A
Balance current: 1-6S

Size: 110x110x31mm

D1

AC/DC
SMART
CHARGER



Charging Power: AC 100W
DC 250W
Charging Current: 10A
Balance current: 1-6S

Size: 126x115x49mm

K1

AC/DC
SMART
CHARGER



Max. charging power: AC 100W
DC 250W x2
Charging current: 10A x2
Balance current: 1-6S

Size: 115x135x49 mm

K2 Air

AC/DC
SMART
CHARGER



Max. charging power: AC 200W
DC 500W x2
Charging current: 20A x2
Balance current: 1-6S

Size: 142x135x64 mm

Q6 Nano

SMART
CHARGER



Charging power: 200W
Charging current: 8A
Balance current: 1-6S

Size: 72x72x33 mm

Air8

SMART
CHARGER



Charging power: 500W
Charging current: 20A
Balance current: 1-8S

Size: 80x80x33 mm

BattAir Plugin



Supported Cells of Battery: 2S/3-4S/5-6S
Supported Battery Type: LiFe, LiPo,
LiHv, ULIHv

Quiescent Current: 50uA
Size: 35x16x9mm/36x19x9mm/36x24x9mm

ESC 70/90



Cont. / Peak Current: 70/120A | 90/180A
Motor type: 540/550/775 Brushed motor
Battery Type: 2-3S LiPo or 6-8Cell NiMH
Applications: 1/8 or 1/10 Various models

Size: 38x31x17mm

H605

SMART
CHARGER



Charging Power: 50W
Charging Current: 5A
Balance current: 1-6S
Bluetooth support: BLE4.0 above

Size: 79x55.7x16.6mm

PD60

USB-C SMART
CHARGER



Charging power: 60W
Charging current: 1A/2A/3A/6A
Balance current: 1-4S

Size: 56x85x21 mm

K4

AC/DC
SMART
CHARGER



Charging power: AC 400W
DC 600W x2
Charging current: 20A x2
Balance current: 1-8S

Size: 176x183x57 mm

D2 Mark II

AC
SMART
CHARGER



Charging Power: 200W
Charging Current: 12A x2
Balance current: 1-6S

Size: 120x108x70

Q8 Max

SMART
CHARGER



Charging power: 1000W
Charging current: 30A
Balance current: 1-8S

Size: 95x95x45 mm

P10

SMART
CHARGER



Charging power: 250W x2
Charging current: 10A x2
Balance current: 1-8S

Size: 91x91x47 mm

P20

SMART
CHARGER



Charging power: 500W x2
Charging current: 20A x2
Balance current: 1-8S

Size: 105x105x47 mm

P30

SMART
CHARGER



Charging power: Single channel Max. 1000W;
Whole model Max. 1500W
Charging current: 30A x2
Balance current: 1-8S

Size: 110x110x65 mm